

UW-403X+

Optical Power Meter (Built-in VFL)



Specifications

Measurement Range	-70 ~ +10dBm	-50 ~ +26dBm
Wavelength Range (nm)	800 ~ 1650nm	
Calibrated Wavelength	850nm, 1300nm, 1310nm, 1490nm, 1550nm, 1625nm	
Detector	InGaAs	
Accuracy	< ± 3% (-10dBm, 22°C)	
Resolution	Linearity : 0.1% (-10dBm 22°C)	
Working Temperature	-10°C ~ +50°C	
Storage Temperature	-20°C ~ +70°C	
Relative Humidity	90% (+30°C)	
Connector	Universal 2.5mm Ferrule	
Power Supply	2 Pcs. AA Batteries	
Working Hours	> 120 Hours (without backlight)	
Weight (gm)	210gm	
Dimension (mm)	77 x 39 x 14mm	
VFL (as Option)	Wavelength: 650nm, Output: 10mW, Frequency: 0Hz/2Hz	

 **Uniway Infocom**
C-9/4, WAZIRPUR INDUSTRIAL AREA,
OPP. BAJAJ SHOWROOM,
Delhi-110052

 **Ph: +91-11-42470111, 9821629809**

 **Email: sales@uniwayinfo.com**

 **Web: www.uniwayinfo.com**