UW-55H

Optical Fiber Splicing Machine PAS- Profile Alignment System Core-to-Core Alignment







- Light weight, easy to carry, compact size
- Recommended for CATV/FTTx
- Splice Time: 7sec, Heat Time: 13sec
- High capacity battery 5200mAh
- Battery Back-up of 300 Splices
- Electrode Life: 5000 Splices
- Rugged Design, Water resistant
- P IP Protection IP 66









Specifications

| Specifications | | |
|--------------------------|--|--|
| Applicable Fibers | SMF, MMF, NZDSF, EDF, DCF, LDF | |
| Average Splice Loss | 0.01dB(SM), 0.01dB(MM), 0.04dB(NZDS), 0.04dB(LDF) | |
| Return Loss | ≥60dB | |
| Tension Test | 2.5N(230gf)(Standard) | |
| Protection Sleeve Lenght | 20mm - 60mm | |
| Typical splicing time | 7 seconds | |
| Typical heating time | 13 seconds | |
| Connectivity Interface | USB | |
| Operating Conditions | -10~+50°C(operation temperature),0~95% RH(humidity), 0~6000m(altitude), Wind: upto 15m/sec | |
| Electrode Life | More Than 5000 Splices | |
| Power Supply | AC adaptor: 100~230V input voltage, 50/60Hz; 7.4V, 5A output voltage(DC) Rechargeable Inner lithium battery: 7.4V, 5200mAh for up to 300 splicing cycles | |
| Monitor | 4.3 inches High Resolution Colorful LCD Display | |
| Fiber Image | X or Y axis Separately views 360 times magnification, or Simultaneously 200 times | |
| Storage of Splice Result | 6,000 groups of latest Splice Results with Date / Time | |
| Splicing Model | Auto, Manual & Full Auto | |
| Dimensions | 120(W)*120(D)*130(H)mm; Package size: 43*32.5*26.5cm | |
| Weight | 1.29kg+0.30kg (battery weight)=1.59kg; Package G.W.: 8kg | |
| Standard Accessories | | |
| No. | Item Quantity | |
| 01 | Splicing Machine UW-55H 01 No. | |
| 02 | High Precision Fiber Cleaver 01 No | |

| No. | ltem | Quan tity |
|-----|-----------------------------------|------------------|
| 01 | Splicing Machine UW-55H | 01 No. |
| 02 | High Precision Fiber Cleaver | 01 No. |
| 03 | Fiber Stripper (3-in-1) | 01 No. |
| 04 | AC Adapter (Charger) | 01 No. |
| 05 | Battery Pack | 01 No. |
| 06 | Spare Electrode | 01 Pair |
| 07 | Cooling Tray | 01 No. |
| 08 | Instruction CD | 01 No. |
| 09 | Quick Reference Guide | 01 No. |
| 10 | Carrying Case with Carrying Strap | 01 No. |
| | | |



C. Ph: +91-11-42470111, 9821629809

Email: sales@uniwayinfo.com

Web: www.uniwayinfo.com

Branch Offices Contact No.

| Kolkata | +91-995 <mark>8480410</mark> |
|------------|------------------------------|
| | +91-9062008500 |
| Mumbai | +91-982148 <mark>6620</mark> |
| Ahmedabad | +91-9821486 <mark>621</mark> |
| Hyderabad | +91-98217594 <mark>81</mark> |
| Bangalore | +91-9971555664 |
| Chandigarh | +91-8054247415 |
| | |